

別表 5 (7-11 関係)

異なる速度における負荷能力

速度 (km/h)	ロードインデックスの変化 (%)									
	ロードインデックス				ロードインデックス ≥122		ロードインデックス ≤121			
	速度区分記号				速度区分記号		速度区分記号			
	F	G	J	K	L	M	L	M	N	P
5	110	110	110	110	110	110	90	90	90	90
10	80	80	80	80	80	80	75	75	75	75
15	65	65	65	65	65	65	60	60	60	60
20	50	50	50	50	50	50	50	50	50	50
25	35	35	35	35	35	35	42	42	42	42
30	25	25	25	25	25	25	35	35	35	35
35	19	19	19	19	19	19	29	29	29	29
40	15	15	15	15	15	15	25	25	25	25
45	13	13	13	13	13	13	22	22	22	22
50	12	12	12	12	12	12	20	20	20	20
55	11	11	11	11	11	11	17.5	17.5	17.5	17.5
60	10	10	10	10	10	10	15.0	15.0	15.0	15.0
65	7.5	8.5	8.5	8.5	8.5	8.5	13.5	13.5	13.5	13.5
70	5.0	7.0	7.0	7.0	7.0	7.0	12.5	12.5	12.5	12.5
75	2.5	5.5	5.5	5.5	5.5	5.5	11.0	11.0	11.0	11.0
80	0	4.0	4.0	4.0	4.0	4.0	10.0	10.0	10.0	10.0
85		2.0	3.0	3.0	3.0	3.0	8.5	8.5	8.5	8.5
90		0	2.0	2.0	2.0	2.0	7.5	7.5	7.5	7.5
95			1.0	1.0	1.0	1.0	6.5	6.5	6.5	6.5
100			0	0	0	0	5.0	5.0	5.0	5.0
105				0	0	0	3.75	3.75	3.75	3.75
110				0	0	0	2.5	2.5	2.5	2.5
115					0	0	1.25	1.25	1.25	1.25
120					0	0	0	0	0	0
125						0		0	0	0
130						0		0	0	0
135									0	0
140									0	0
145										0
150										0

注：速度区分記号が「Q」以上のタイヤの場合の荷重変化は行わない。